

Serial No.: 10/568,319  
Art Unit: 2624

### **AMENDMENTS TO THE CLAIMS:**

This listing of the claims will replace all prior versions, and listings, of the claims in this application:

#### **Listing of Claims:**

1. (Currently amended) A method in a digital image processing chain in a device for adjusting a colour balance comprising; ~~in which method~~

- inputting to the device the subject is imaged by pixels to form value-sets of the colour components R, G, B ~~(R, G, B)~~ which have been formed by imaging a subject by pixels,
- forming component-specific histograms ~~are formed~~ from the value-sets of the colour components ~~(R, G, B),~~
- forming cumulative histograms ~~are formed~~ from the component-specific histograms,
- defining an the illumination colour ~~(R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>)~~ corresponding to at least one colour component ~~is defined~~ from the cumulative histograms,
- defining a gain factor adjusting the colour balance for at least two colour components using a target colour ~~(R<sub>tgt</sub>, G<sub>tgt</sub>, B<sub>tgt</sub>)~~ and the defined illumination colour ~~(R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>)~~ ~~are defined for at least two colour components (R, G, B) a gain factor (G<sub>R</sub>, G<sub>G</sub>, G<sub>B</sub>) adjusting the colour balance,~~

characterized that, in the method

- defining from an essentially flat area of a colour curve at the ends of the cumulative histograms ~~a such~~ a common point  $h_i$ , at which the colour-component wise pixel-intensity values  $C_i$ ,  $C_{i+1}$ , corresponding to the consecutive points  $h_i$ ,  $h_{i+1}$ , meet the criteria conditions set for ~~them in the case of~~ at least one colour component ~~(R, G, B),~~ is defined from the essentially flat area of the colour curve at the ends of the cumulative histograms, and

Serial No.: 10/568,319  
Art Unit: 2624

- setting the a colour-component wise intensity value  $C_i$ , corresponding to athe common defined point  $h_i$  is set for the at least one colour component ( $R, G, B$ ), to correspond to the illumination colour ( $R_{ill}, G_{ill}, B_{ill}$ ).

2. (Currently amended) A method according to Claim 1, ~~characterized in that~~ further comprising defining the illumination colour ( $R_{ill}, G_{ill}, B_{ill}$ ) is defined from the cumulative histograms, by searching for a the smallest index  $i$  meeting the following sub-criteria:

1) a the ratio  $r_C$  of the pixel values  $C_i, C_{i+1}$ , corresponding to two consecutive points  $h_i, h_{i+1}$  selected according to a set interval division, is less than a first threshold value  $t_1$  for ~~set for them,~~ in each colour component ( $R, G, B$ ), i.e.,

$$r_C = \frac{C_i}{C_{i+1}} < t_1, C = (R, G, B),$$

2) ~~such caused a~~ sum of the ratios  $r_C$  corresponding to the pixel values  $C_i, C_{i+1}$  is less than a second threshold value  $t_2$  ~~set for them,~~ where  $R_i, G_i, B_i$  correspond to  $C_i$  and  $R_{i+1}, G_{i+1}, B_{i+1}$  correspond to  $C_{i+1}$ ,

$$\frac{R_i}{R_{i+1}} + \frac{G_i}{G_{i+1}} + \frac{B_i}{B_{i+1}} < t_2, \text{ and}$$

3) the ratio of the relative speeds of change of the pixel values  $C_i, C_{i+1}$  between the maximum pixel-value change and the minimum pixel-value change is less than a third threshold value  $t_3$  ~~set for it,~~

$$\frac{\max((C_i - C_{i+1}) / C_{i+1}), \text{ in which } C \in R \parallel G \parallel B}{\min((C_i - C_{i+1}) / C_{i+1}), \text{ in which } C \in R \parallel G \parallel B)} < t_3, \text{ and}$$

in which the intensity values  $C_i$  of each colour component corresponding to the point  $h_i$ , meeting the conditions 1 - 3, are set to correspond to the illumination colour ( $R_{ill}, G_{ill}, B_{ill}$ ).

3. (Currently amended) A method corresponding to Claim 2, ~~characterized in that~~ wherein the first threshold value  $t_1$  varies within the range 1.0 to 1.5 ~~1,0—1,5, preferably within the range 1,01—1,2.~~

Serial No.: 10/568,319  
Art Unit: 2624

4. (Currently amended) A method according to Claim 2, ~~characterized in that~~ wherein the second threshold value  $t_2$  varies within the range 3.0 to 4.0 ~~3,0—4,0, preferably within the range 3,0—3,5.~~
5. (Currently amended) A method according to Claim 2, ~~characterized in that~~ wherein the third threshold value  $t_3$  varies within the range 3.0 to 5.0 ~~3,0—5,0, being preferably about 4,0.~~
6. (Currently amended) A method according to Claim 1, ~~characterized in that, in the method,~~ further comprising performing a pedestal elimination (PE) ~~is also performed~~ on the pixel values of a ~~the~~ raw matrix, prior to the colour-balance adjustment ~~(CBC)~~.
7. (Currently amended) A method according to Claim 6, ~~characterized in that~~ comprising performing the pedestal elimination, ~~(PE) is performed~~ at least partly linearly, ~~for example, in such a way that~~
- when the pixel-value level of a colour component ~~(R, G, B)~~ is below a threshold value ~~(t)~~ set for it, an offset ~~(p)~~ is deducted by direct subtraction, and, then, at a same time, deducting after the set threshold value (t),
  - the offset ~~(p)~~ is deducted, however, at the same time and gaining the pixel-values in such a way that the maximum pixel-value level does not substantially diminish.
8. (Currently amended) A method according to Claim 1, ~~characterized in that, in the method,~~ further comprising performing a vignetting elimination procedure (VE) ~~is also performed,~~ preferably after the pedestal elimination (PE) and before the colour-balance adjustment (CBC).
9. (Currently amended) A method according to Claim 8, ~~characterized in that~~ further comprising using a spatially varying offset and a pixel-value gain factor ~~(vf)~~ are used in the vignetting elimination procedure ~~(VE)~~.
10. (Currently amended) A method according to Claim 9, ~~characterized in that~~ further comprising developing the gain factor ~~(vf) is developed~~ separately for each colour component ~~(R, G, B)~~.

Serial No.: 10/568,319  
Art Unit: 2624

11. (Currently amended) A method according to Claim 1, ~~characterized in that, in connection with the method, further comprising performing~~ a dark-colour correction procedure ~~is also performed~~, in which, as sub-stages,

- ~~such pixel values meeting a threshold condition (dpee) set for them are determined sought~~ from the cumulative histogram,
- ~~a the~~ defined darkest colour component is stretched using an offset of a defined magnitude towards the dark end of the histogram, while also processing the other colour components in ~~a the~~ same proportion, and
- readjustment is performed on the gains ~~(G<sub>R</sub>, G<sub>G</sub>, G<sub>B</sub>)~~ of the conversion functions.

12. (Currently amended) A method according to Claim 1, ~~characterized in that~~ further comprising defining a median pixel value ~~is defined~~ for each colour component ~~(R, G, B)~~ and, if ~~a the~~ median pixel value of ~~a the~~ selected reference component and ~~a the~~ median pixel value of ~~a the~~ colour component ~~(R, G, B)~~ differ from each other in a set manner, adjusting the gains ~~(G<sub>R</sub>, G<sub>G</sub>, G<sub>B</sub>) are adjusted~~, in order to reduce the difference.

13. (Currently amended) A method according to Claim 1, ~~characterized in that the method also includes~~ further comprising performing a gamma-correction stage ~~GC~~, in which

- ~~a shot type, which can be, for example, normal, backlight, or low contrast, is defined from the cumulative histograms,~~
- on the basis of the shot-type definition, the gamma value selected for use in the gamma correction is reduced; in proportion to an amount ~~how much the image is to should be brightened, wherein the which gamma value is can vary, for example, in the range of 0.10 to 0.80~~ ~~0,10—0,80, preferably in the range 0,20—0,60.~~

14. (Currently amended) A method according to Claim 1, ~~characterized in that,~~ further comprising filtering, prior to the formation of the cumulative histograms, at least one pixel value ~~such pixel values (G<sub>(e)</sub>) out of at least one value set;~~ in which the pixel value of the same image

Serial No.: 10/568,319  
Art Unit: 2624

point (15.1) in even one value set meets a selected criterion, are filtered out of at least one value set.

15. (Currently amended) An apparatus system in a digital image processing chain (10) for adjusting a colour balance, ~~which system includes comprising:~~

- an input configured to image means for imaging a subject by pixels to form value-sets of the colour components R, G, B (~~R, G, B~~),
- a first processing element configured to form means for forming component wise histograms from the value-sets of the colour components (~~R, G, B~~),
- a second processing element configured to form means for forming cumulative histograms from the component wise histograms,
- a third processing element configured to define an means for defining the illumination colour (~~R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>~~) corresponding to at least one colour component from the cumulative histograms,
- a fourth processing element configured to define means for defining a gain factor (~~G<sub>R</sub>, G<sub>G</sub>, G<sub>B</sub>~~) for at least two colour components (~~R, G, B~~) adjusting the colour balance using target colour (~~R<sub>tgt</sub>, G<sub>tgt</sub>, B<sub>tgt</sub>~~) and the defined illumination colour (~~R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>~~),

characterized in that, the system also includes

- a fifth processing element configured to define means for defining, from an the essentially flat area of the colour curve at an the end of the cumulative histograms, such a point  $h_i$ , in which the colour-component wise pixel-intensity values  $C_i, C_{i+1}$ , corresponding to the consecutive points  $h_i, h_{i+1}$ , are arranged to meet the criteria conditions set for them for ~~in the case of~~ at least one colour component (~~R, G, B~~), and
- a sixth processing element configured to set means for setting the color-componentwise intensity value  $C_i$ , corresponding to the defined common point  $h_i$ , for at least one color component (~~R, G, B~~) to correspond to the illumination colour (~~R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>~~).

16. (Currently amended) An apparatus-system according to Claim 15, ~~characterized in that wherein the apparatus system~~ also includes a functionality, arranged before the colour-balance adjustment-~~(CBC)~~, for performing pedestal elimination-~~(PE)~~ on the pixel values of a the raw matrix.
17. (Currently amended) An apparatus-system according to Claim 15, ~~characterized in that wherein the apparatus system~~ also includes a seventh processing element configured to perform means for performing vignetting elimination-~~(VE)~~, which ~~are preferably arranged~~ after the pedestal elimination-~~(PE)~~ and before the colour-balance adjustment-~~(CBC)~~.
18. (Currently amended) An apparatus-system according to Claim 15, ~~characterized in that wherein the apparatus system~~ comprises also includes means for correcting a dark colour.
19. (Currently amended) An apparatus-system according to Claim 15, ~~characterized in the wherein the apparatus system~~ comprises also includes means for filtering out prior to the formation of the cumulative histograms at least such pixel values-~~(G<sub>(s)</sub>)~~ of at least one value set, in which a ~~the~~ pixel value of the same image point-~~(15.1)~~ in at least ~~even~~ one value set meets a selected criterion.
20. (Currently amended) An equipment for adjusting colour balance, in which the equipment includes a digital image-processing chain-~~(10)~~, in which the chain-~~(10)~~ includes
- means for imaging a subject by pixels to form value-sets  $[R], [G], [B]$  of the colour components R, G, B ~~(R, G, B)~~,
  - means for forming component wise histograms from the value-sets of the colour components ~~(R, G, B)~~,
  - means for forming cumulative histograms from the component wise histograms,
  - means for defining a ~~the~~ illumination colour-~~(R<sub>ill</sub>, G<sub>ill</sub>, B<sub>ill</sub>)~~ corresponding to at least one colour component from the cumulative histograms,

Serial No.: 10/568,319  
Art Unit: 2624

- means for defining a gain factor  $(G_R, G_G, G_B)$  for at least two colour components  $(R, G, B)$  adjusting the colour balance using a target colour  $(R_{tgt}, G_{tgt}, B_{tgt})$  and defined illumination colour  $(R_{ill}, G_{ill}, B_{ill})$ ,

~~characterized in that the equipment also includes~~

- means for defining, from ~~an~~ the essentially flat area of ~~a~~ the colour curve at ~~an~~ the end of the cumulative histograms, ~~such~~ a point  $h_i$ , in which the colour-component wise pixel-intensity values  $C_i, C_{i+1}$ , corresponding to the consecutive points  $h_i, h_{i+1}$ , are arranged to meet the criteria conditions ~~for set for them in the case of~~ at least one colour component  $(R, G, B)$ , and

- means for setting the color-componentwise intensity value  $C_i$  corresponding to the defined common point  $h_i$ , for at least one color component  $(R, G, B)$  to correspond to the illumination colour  $(R_{ill}, G_{ill}, B_{ill})$ .

21. (Currently amended) A computer readable storage medium embodied with a computer program comprising: Software means for implementing the method according to Claim 1, in which the include

- softwarean interface for receiving image data,

- software for inputtingimaging a subject by pixels to form value-sets of the colour components  $(R, G, B)$  which have been formed by imaging a subject by pixels,

- software for forming component wise histograms from the value-sets  $R, G, B$   $\{R\}, \{G\}, \{B\}$  of the colour components  $(R, G, B)$ ,

- software for forming cumulative histograms from the component wise histograms,

- software for defining the illumination colour  $(R_{ill}, G_{ill}, B_{ill})$  corresponding to at least one colour component from the cumulative histograms,

Serial No.: 10/568,319  
Art Unit: 2624

- software for defining a gain factor  $(G_R, G_G, G_B)$  for at least two colour components  $(R, G, B)$  adjusting the colour balance using target colour  $(R_{tgt}, G_{tgt}, B_{tgt})$  and defining ~~defined~~ illumination colour  $(R_{ill}, G_{ill}, B_{ill})$ ,

characterized in that, ~~in the software means, there are also arranged~~

- software for defining, from an ~~the~~ essentially flat area of the colour curve at the end of cumulative histograms, ~~such a point  $h_i$~~ , in which ~~the~~ colour-component wise pixel-intensity values  $C_i, C_{i+1}$ , corresponding to ~~the~~ consecutive points  $h_i, h_{i+1}$ , are arranged to meet ~~the~~ criteria conditions for set for them in the case of at least one colour component  $(R, G, B)$ , and

- software for setting the color-componentwise intensity value  $C_i$ , corresponding to the defined common point  $h_i$ , for at least one color component  $(R, G, B)$  to correspond to the illumination colour  $(R_{ill}, G_{ill}, B_{ill})$ .

22. (New) A device in a digital image processing chain for adjusting a colour balance comprising:

- means for inputting value-sets of colour components formed by imaging a subject by pixels,

- means for forming component wise histograms from the value-sets of the colour components,

- means for forming cumulative histograms from the component wise histograms,

- means for defining an illumination colour corresponding to at least one colour component from the cumulative histograms,

- means for defining a gain factor for at least two colour components adjusting a colour balance using a target colour and the defined illumination colour,

- means for defining, from an essentially flat area of a colour curve at an end of the cumulative histograms a point  $h_i$  in which colour-component wise pixel-intensity values  $C_i$ ,



Serial No.: 10/568,319  
Art Unit: 2624

$C_{i+1}$  corresponding to consecutive points  $h_i, h_{i+1}$  arranged to meet criteria conditions for at least one colour component, and

- means for setting the color-componentwise intensity value  $C_i$  corresponding to the defined common point  $h_i$ , for at least one color component to correspond to the illumination colour.

23. (New) A device according to Claim 22, wherein the device comprises a functionality, arranged before the colour-balance adjustment, for performing pedestal elimination on pixel values of a raw matrix.

24. (New) A device according to Claim 22, wherein the device comprises means for performing vignetting elimination, which are preferably arranged after the pedestal elimination and before the colour-balance adjustment.

25. (New) A device according to Claim 22, wherein the device comprises means for correcting a dark colour.

26. (New) A device according to Claim 22, wherein the device comprises means for filtering out prior to the formation of the cumulative histograms at least such pixel values of at least one value set, in which the pixel value of the same image point in even one value set meets a selected criterion.

27. (New) A device according to Claim 22 further comprising means for imaging a subject by pixels to form value-sets of the colour components.